

SL. No. 08

Schedule for the work:- "M/R to Cart Bridge at ch.1797.00 of G.B.C. under Chandrakona town section of K.C. Sub Divn. No.-VII,Amlagora,Paschim Medinipur during the year 2016-17."

SL NO	DESCRIPTION OF ITEM	QUANTITY	UNIT	RATE Rs P	UNIT	AMOUNT Rs P
1	Stripping off worn out plaster and raking out joints of walls, ceilings etc. upto any height and in any floor including removing rubbish within a lead of 75m as directed.	174.94	m2	19.00	m2	3323.86
2	Cleaning the concrete surface by removing dirt and debris, marking defective locations and removing loose concrete by careful stripping untill hard surface is exposed, cutting the concrete to regular shape, wire brushing the exposed surface and removing debris from site complete as per direction of the Engineer - in - Charge.	35.20	m2	96.00	m2	3379.20
3	Applying epoxy based reactive joining agent for joining the old concrete with fresh concrete to be applied within manufactured specified time as per manufacture specification (0.4Kg/m2 of concrete surface) Note: Applicable only when the full diameter reinforcement steel is exposed)	84.70	m <sup>2</sup>	356.00	m <sup>2</sup>	30153.20
4	Extra for Rusticated plaster (over rate of corresponding item of plaster) (b) With stone chips (Cement 0.086 Cu.m/100Sq.m)	84.70	m2	62.00	m2	5251.40
5	Plaster (to wall, floor, ceiling etc.) with sand and cement mortar including rounding off or chamfering corners as directed and raking out joints including throating, nosing and drip course, scaffolding/staging where necessary (Ground floor).[Excluding cost of chipping over concrete surface] (ii) With 1:4 cement mortar (a) 20 mm thick plaster	174.94	m2	191.00	m2	33413.54
6	Artificial stone in floor, dado, staircase etc with cement concrete (1:2:4) with stone chips, laid in panels as directed with topping made with ordinary or white cement (as necessary) and marble dust in proportion (1:2) including smooth finishing and rounding off corners including raking out joints or roughening of concrete surface and application of cement slurry before flooring works using cement @ 1.75 kg/sq.m all complete including all materials and labour. In ground floor. 3 mm. thick topping (High polishing grinding on this item is not permitted with ordinary cement). Using grey cement (iii) 35 mm. thick	35.20	m2	369.00	m2	12988.80
7	Neat cement punning about 1.5mm thick in wall,dado,window sill,floor etc. NOTE:Cement 0.152 cu.m per100 sq.m.	32.60	m2	38.00	m2	1238.80

SL NO	DESCRIPTION OF ITEM	QUANTITY	UNIT	RATE Rs P	UNIT	AMOUNT Rs P
8	Acrylic Distemper to interior wall, ceiling with a coat of solvent based interior grade acrylic primer (as per manufacturer's specification) including cleaning and smoothing of surface. Two Coats	207.60	m2	76.00	m2	15777.60
9	Protective and Decorative Acrylic exterior emulsion paint of approved quality, as per manufacturer's specification and as per direction of EIC to be applied over acrylic primer as required. The rate includes cost of material, labour, scaffolding and all incidental charges but excluding the cost of primer. In Ground floor (Two Coat) a) Normal Acrylic Emulsion	207.60	m2	73.00	m2	15154.80
10	Painting block letters or digits in Black Japan or any approved paint as per direction c) Size above 4 cm. and upto 5 cm	100.00	nos	10.00	nos	1000.00
Total = Rs.						121681.20

Grand Total =Rs. **121681.20**

Say, =Rs. **121681.00**

(Rupees one lakh twenty one thousand six hundred and eighty one only)

*Amy...*  
Executive Engineer  
K.C. Division No. I  
Amlagora, Paschim Medinipur  
#01/09/16

I/We do here by agree to execute the above work @ ..... % Above/Low/At per than the Schedule of Rates attached herewith .

Signature of the Contractor(s)